

Declaration of Compliance

Name and address of the business operator issuing the declaration of compliance;	Polynova Nissen AB Vretensborgsvägen 28, 7tr SE-126 30 Hägersten																			
Identity of the materials or articles	Polyethylene Art.Nr: 4100001-3																			
Date of issuing the DoC	(20260319)																			
Conformity with Legislation	EU regulation 1935/2004, Plastics regulation EU/10/2011 as amended. We confirm that the plastic materials or articles, products from intermediate stages of manufacture or the substances meet the relevant requirements laid down in Regulation (EU) No 10/2011 and in Article 3, 11(5), 15 and 17 of Regulation (EC) No 1935/2004.																			
Good Manufacturing Practice	The manufacturer follow the requirements in EU regulation 2023/2006 in the production of the material / article covered by this Declaration.																			
Information relative to the substances used or products of degradation	All substances used are in the Union list, EU/10/2011, annex 1, and are not migrating above the migration limits if the material / article is used according to given restrictions for use.																			
Information relative to the substances which are subject to a restriction in food; Dual use additives	No Dual use additives																			
Intended for the following types of food	Aqueous, acidic, alcoholic, fatty, dry																			
Intended for the following times and temperatures at use	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;">Food simulants:</td> <td style="width: 25%;">10% Ethanol</td> <td style="width: 25%;">3% Acetic Acid</td> <td style="width: 25%;">Veg Oil</td> </tr> <tr> <td>Time</td> <td>10d</td> <td>10d</td> <td>10d</td> </tr> <tr> <td>Temp C</td> <td>40</td> <td>40</td> <td>40</td> </tr> <tr> <td>Results mg/dm²</td> <td><10</td> <td><10</td> <td><10</td> </tr> </table>				Food simulants:	10% Ethanol	3% Acetic Acid	Veg Oil	Time	10d	10d	10d	Temp C	40	40	40	Results mg/dm ²	<10	<10	<10
Food simulants:	10% Ethanol	3% Acetic Acid	Veg Oil																	
Time	10d	10d	10d																	
Temp C	40	40	40																	
Results mg/dm ²	<10	<10	<10																	

Highest Surface to volume ratio for which compliance is verified	6 dm ² /dm ³
Functional barrier	Functional barrier is not used.
Other relevant specifications on the use of the article	Single Use Hot fill 100 C max 15 min
Supporting documentation availability	Supporting documentation (detailed information) will be available on request by authorities within 1–2 weeks.
Signing	<p>Polynova Nissen AB</p> <p>Polynova Nissen AB Box 42016 126 12 Stockholm</p> <p>Vretensborgsvägen 28, 7tr SE-126 30 Hägersten</p>